

# Power distribution for IT equipment

Basic  
In-Line Metered  
Metered Input

Metered Outlet  
Switched  
Managed

## Rack PDU G3+ 2019 Version



# EATON

Powering Business Worldwide



# Rack PDU G3+

New features 2019	G3+ range	G3 range
<b>Extra flat breaker:</b> avoid accidental tripping	✓	
<b>P-Lock &amp; eGrip plugs:</b> secure your IEC power cable	✓	
<b>Alternating Phase 3P-32A:</b> Natural load balancing	✓	
<b>Stronger mounting system</b>	✓	
<b>Daisy chain up to 3 sensors:</b> Collect more environmental data's per rack	✓	✓ <sup>1</sup>
<b>Cybersecurity enhancement</b>	✓	✓ <sup>1</sup>
<b>USB Smart Commissioning Tool</b> (Coming later): Fast individual configuration deployment	✓	✓ <sup>1</sup>

1. available with the latest firmware 4.x or later

## Outlets with dual built-in security mechanism New

**eGrip system** to secure standard IEC power cables (Eaton's patent-pending) with a lever-actuated grip that's integrated into each outlets. Once the levers click into the grip position, the plugs are secured from accidental disconnect due to bumps or vibrations. Outlets are also compatible with a **locking system** using IEC P-Lock power cables.




## Hot-swap capability

Eaton's hot-swap control module can be replaced without the need to power down your rack. Increase uptime while enhancing service ability and saving on unnecessary service calls. The menu-driven pixel display allows for easy setup and troubleshooting.



## Daisy chain eight units from one IP address

Eaton's new patented daisy-chain capability allows up to eight ePDUs to share the same network connection and IP address. Eaton technology provides a 87% percent reduction in network infrastructure costs.



## Natural load balancing by design New

Alternating phase per section on all 3 Phase 32A ePDUs to naturally balanced the rack power load using shorter cables.



## Quickly identify load protection and phase with color coded sections

One color for each phase, one letter per breaker protection.



## Provide zero interference into the rail space New

New extra flat breakers and low-profile form factor chassis to avoid accidental tripping.

# Upgrade your power distribution

## Control power at server level

**Outlet switching:** Remotely control devices by powering on or off individual outlets. Save time and operating costs by rebooting machines from your control center without costly site visits.

**Sequential start up:** Make sure your servers start sequentially to avoid in rush current and start your database before the application.

**Turn off unused outlets:** Control unauthorized use.

## Daisy Chain Sensor New

Daisy chain up to 3 sensors per rack PDU to get more environmental data's from your rack. Each sensor has 1 temperature probe, 1 humidity probe and 2 dry contacts.

## Cybersecurity enhancement New

The firmware is updated on regular basis to keep the ePDU cybersecurity to highest standard

## High 60°C operating temperature

Fully functional in high operating temperature environments, resulting in reduced cooling costs.

## Universal mounting system New

Vertical units (0U) include both rear & side button mounting system stronger than before and Eaton's patented variable clip feet. Horizontal units (1U/2U) come with rack ear support.



## ±1% Accurate Power Measurement

ePDU G3 provides one percent revenue-grade power monitoring for higher accuracy in department billing or colocation data centers. Effectively measure power usage to all outlets or individual outlets.



## Device reboot and measurement across A and B feed

When connecting multiple source input servers to an A and B feed power source, the daisy-chain capability allows you to group power supplies across the ePDU. As a result, all the power supplies are controlled with a single action, which saves time rebooting servers with two to six power supplies. The power consumption is available for each device.





# ePDU G3+ Key features & technical specification



	Basic	In-Line Metered	Metered Input	Metered Outlet	Switched	Managed
<b>Basic features</b>						
Outlets with <b>dual built-in security mechanism</b> eGrip & P-Lock	✓	NA	✓	✓	✓	✓
<b>Colour-coded outlet</b> and branch circuits for simple load balancing	✓	NA	✓	✓	✓	✓
<b>60°C</b> Operating temperature	✓	✓	✓	✓	✓	✓
Universal rack <b>mounting system</b> (button & clip feet)	✓	✓	✓	✓	✓	✓
Alternating phase per sections (available on 3Phase 32A PDU)	✓	✓	✓	✓	✓	✓
<b>Hot-Swap Control module with Advanced LCD + Optional Temp/Humidity sensor</b>			✓	✓	✓	✓
<b>±1% IEC Class 1 Billing Grade Accuracy</b> for V, W, A and kWh & Cisco <b>EnergyWise</b> compliant		✓	✓	✓	✓	✓
<b>Phase Metering, Circuit Breaker Current Metering and Input Metering</b>		✓	✓	✓	✓	✓
<b>Daisy-Chain</b> up to 8 ePDUs, reduce network infrastucture costs		✓	✓	✓	✓	✓
Power chain monitoring & Real time Intelligence on your Data Center, via Eaton and advanced action on <b>virtual environment</b> via <b>Eaton IPM Edition</b>		✓	✓	✓	✓	✓
<b>Protocols &amp; standards</b> HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DHCP, LDAP, RADIUS, DHCP 66/67 for Mass Configuration		✓	✓	✓	✓	✓
<b>Advanced features</b>						
Circuit Breaker Status Monitoring				✓	✓	✓
Outlet and IT Equipment Metering across A and B feed				✓		✓
<b>Level 3 PUE</b> measurements				✓		✓
<b>Turn off unused outlets</b> to control commissioning					✓	✓
Outlet and IT Equipment <b>Switching/reboot/sequencing</b> across A and B feed					✓	✓

	Input Type / Rating (A)	Outlet type: Qty	Breakers	Nominal Power	Basic p/n		In-Line Metered & Dual p/n		Metered Input p/n		Metered Outlet p/n		Switched p/n		Managed p/n				
					Dimensions L x W x D, mm	Dimensions L x W x D, mm	Dimensions L x W x D, mm	Dimensions L x W x D, mm	Dimensions L x W x D, mm	Dimensions L x W x D, mm	Dimensions L x W x D, mm	Dimensions L x W x D, mm	Dimensions L x W x D, mm	Dimensions L x W x D, mm					
1 Phase	C14 10A	8xC13		2.3kW	EBAB02	443x19"x53			1U	EMIH02	10x19"x203								
		12xC13		2.3kW	EBAB19	443x19"x53													
		16xC13		2.3kW	EBAB03	704x52x53				EMIB03	1070x52x53		ESWB03	1154x52x53	EMAB03	1154x52x53			
	C20 16A	FlexPDU*	8xFR: 1xC19		3.7kW	1U	EFLX8F	10x19"x80											
			8xGE: 1xC19		3.7kW	1U	EFLX8D	10x19"x80											
			6xUK: 1xC19	2 single pole	3.7kW		EFLX6B	52x19"x120											
	IEC60309 16A	12xC13: 1xC19	2 single pole	3.7kW	1U	EFLX12I	10x19"x80												
		16xC13		3.7kW		EBAB21	704x52x53												
		8xC13		3.7kW					1U	EMIH28	10x19"x203		1U	ESWH28	10x19"x203	1U	EMAH28	10x19"x203	
	IEC60309 32A	20xC13: 4xC19		3.7kW		EBAB22	1070x52x53				EMIB22	1070x52x53	EMOB22	1604x52x53	ESWB22	1604x52x53	EMAB22	1604x52x53	
		20xC13 : 4xC19		3.7kW		EBAB04	1070x52x53				EMIB04	1070x52x53		ESWB04	1604x52x53	EMAB04	1604x52x53		
		1EC60309		3.7kW															
3 Phase	2 x IEC60309 16A	2xIEC60309		3.7kW															
	IEC60309 32A	12xC13 : 4xC19	2 single pole	7.4kW						EMIB06	1070x52x53								
		20xC13 : 4xC19	2 single pole	7.4kW		EBAB05	1070x52x53			EMIH06	20x19"x127		EMOB05	1604x52x53	ESWB05	1604x52x53	2U	EMAH06	20x19"x225
		28xC13 : 4xC19	2 single pole	7.4kW						EMIB05	1154x52x53						EMAB05	1604x52x53	
	IEC60309 32A	36xC13 : 6xC19	2 single pole	7.4kW		EBAB08	1604x52x53				EMIB08	1604x52x53					EMAB71	1829x52x53	
		1EC60309		7.4kW															
2 x IEC60309 32A		2xIEC60309		7.4kW															
3 Phase	IEC60309 16A	21xC13 : 3xC19		11kW		EBAB20	1070x52x53			EMIB20	1070x52x53	EMOB20	1604x52x53	ESWB20	1604x52x53	EMAB20	1604x52x53		
		36xC13 : 6xC19		11kW		EBAB00	1604x52x53			EMIB00	1829x52x53								
	IEC60309 32A Alternating phase per section	3xC13 : 6xC19	6 single pole	22kW		EBAB01	704x52x53												
		6xC13 : 12xC19	6 single pole	22kW							EMIB07	1604x52x53							
		18xC13 : 6xC19	6 single pole	22kW													EMAB33	1829x52x65	
		12xC13 : 12xC19	6 single pole	22kW							EMIB12	1604x52x53					EMAB12	1829x52x65	
		24xC13 : 6xC19	6 single pole	22kW		EBAB32	1154x52x53				EMIB32	1604x52x53							
		30xC13 : 12xC19	6 single pole	22kW							EMIB34	1829x52x65							
		1EC60309		22kW															
		2 x IEC60309 32A	2xIEC60309		22kW														

\* Basic G3 features not applicable for the FlexPDU range  
All standard ePDUs come with 3m cable

Need Something Special? We make your custom ePDUs, please contact your local reseller.  
Standard models above are stocked in Europe.



Eaton ePDU Basic G3 has a compliant environmental declaration

# ePDU G3 Accessories

Accessories	Part Number	Benefits
Environmental Monitoring Probe (EMP) Gen 2	EMPDT1H1C2	Get live measurement on temperature, humidity, set threshold and be notified in real time
Adaptor Fast Ethernet Gigabit	GBCONV	Quick and easy way to upgrade your 10/100 Mb network interface G3 ePDU to Gigabit speed
ePDU to UPS cables	CBL2OUT32 CBL3OUT32	Connect an ePDU 32A input to the hardware output UPS
Water leak detector*	WLD012	Detect floods and water leaks
Door contact sensor*	DCS001	Monitor your rack access


\*Door contact sensor and water leak detector can be connected through EMPDT1H1C2 dry contacts



GBCONV



EMPDT1H1C2



DCS001\*



WLD012\*



CBL2OUT32



CBL3OUT32



All ePDU G3 come with a 2 years warranty as standard.  
Standard product Warranty can be extended of 1 additional year (Warranty+1) or 3 additional years (Warranty+3)



# Need Something Special? Your perfect Rack PDU on demand

Dedicated engineering teams to create your perfect Rack PDU on demand. Specific configurations or complete engineering projects

Typical requirements:

- Halogen free material, national socket types, specific number of C13/C19 outlets
- Colored ePDUs on demand to easily identify power source feed

**New** Dual ePDU packaging on demand to reduce environmental impact.

# Add power redundancy solution for mono power supply devices

Eaton ATS are designed to provide power supply redundancy for single connection equipment. With ATS, power from two independent sources can be supplied to IT equipment, which have only one input power supply.



Both sources (primary and secondary) are connected in a straightforward manner to the ATS in the base of the rack. The Eaton ATS then controls the redundancy of this electrical power supply.

**If the primary source fails, transfer to the secondary source is automatic and instantaneous.**

# IPM Editions, Understand and Manage your power infrastructure

IPM Understand Edition helps to bridge the gap between facility and IT management by providing you just enough information, when you need it and where you need it.

## Understand Edition

Understand your power chain infrastructure



- Monitoring of Eaton and many 3rd party power devices
- Power & Environmental reports
- Trending analysis
- Control your load balancing and power redundancy

## Eaton collaborates with the leaders in converged and hyper-converged infrastructures

Our lab-validated power management solutions ensure high uptime of IT systems and data integrity in case of power and environmental issues.





## New Rack PDU Selector

[rackpduselector.eaton.com/gb](http://rackpduselector.eaton.com/gb)

From, input plugs to form factors and measurement features, Eaton's RackPDU selector tool can help you find the right solution for your specific IT needs.



[www.eaton.eu/ePDUG3](http://www.eaton.eu/ePDUG3)

Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions. Only order confirmations and technical documentation by Eaton is binding. Photos and pictures also do not warrant a specific layout or functionality. Their use in whatever form is subject to prior approval by Eaton. The same applies to Trademarks (especially Eaton, Moeller, and Cutler-Hammer). The Terms and Conditions of Eaton apply, as referenced on Eaton Internet pages and Eaton order confirmations.

**Eaton**  
EMEA Headquarters  
Route de la Longeraie 7  
1110 Morges, Switzerland  
Eaton.eu

© 2019 Eaton  
All Rights Reserved  
Printed in Europe  
Publication No. BR155022EN  
June 2019

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

